



# Foanfrax



#### **Overview**

Technology

Foamfrax Process

- **OBenefits**
- Product Forms
- Case Studies
- Target Markets &Applications








# Technology

- Proprietary Technology Encapsulates Fibers in Foam Binder Matrix
- Unifrax Holds the Technology License for the Refractory Market, Global Agreement
- Foamfrax Utilizes Proprietary Binders and Equipment.
- Installed by Unifrax Licensed Distributor/Contractors





# **Foamfrax Process**







#### **Benefits**

- Speed of installation
- Low airborne fiber levels
- Fuel/Energy efficiency
- Lining upgrades over existing hard refractory and RCF linings.
- Backup lining for gunnite and rammed plastics
- Lighter (8pcf 25pcf) than dense refractories
- Monolithic ceramic fiber lining system
- Well suited for intricate geometries
- Incorporates a level of safety over other installed materials



#### **Product Forms**

- Foamfrax Grade I (2300° F)
- Foamfrax Grade II (2600° F)
- Foamfrax Grade III (3000° F)
- Foamfrax RG (1800° F)
- Foamfrax RG+ (2300° F)
- Foamfrax HD (2300°, 2600° &3000°)
- Isofoam (2300° F) Low Bio-Persistent Fiber
- Isofoam RG (1800° F) Low
   Bio-Persistent Fiber







# .....

# Foamfrax Veneer Applications

## <u>Advantages</u>



- Increased Efficiency
- Rapid installation speed, minimum down time
- Lining upgrades
- Postpone major capital investment
- Maintenance tool





# **Case Study (Veneer)**

- Unit: Tunnel Kiln
- Operating Temperature:2100°F
- Scope: 2" thick veneer over refractory
- Lining System: Foamfrax
   Grade I







# Results

- Because there is less temperature variation within the tunnel kiln the result is a more consistent/controlled burn with less color variation in the finished product.
- Kiln throughput was increased from 24 cars/day to 26 cars/day, an 8.3% productivity gain.
- Fuels savings of 3% 4% per 1000 bricks produced.






# **Full Thickness Linings**

# <u>Advantages</u>

Installation rates up to

1500 board feet/ Hr.

- MonolithicConstruction
- Composite LiningSystem
- Anchors Unexposed








# **Case Study (Full Thickness)**

- Operating temperature:2300°F
- Scope: 13-1/2" Composite
   Sidewall Lining
  - > 7" Foamfrax Grade I
  - ➤ 6-1/2" Foamfrax Grade II
- Anchoring System
  - ➤ Inconel 601 "V" Anchors








# Comparison

13-1/2" Firebrick

7" Grade I & 6.5" Grade II








#### Results

- Improved throughput due to reduced heat loss.
- Potential for shorter firing cycles due to reduced heat storage.
- Fuel Savings offset price of Foamfrax.







Furnace Audit Program V2.0

**Furnace Cycle:** Batch - Hot Ramp Down

Temp. °F

2300

\$8,00 per 10<sup>6</sup>BTU

106 BTU/(ft2.hr)

245 BTU/(ft2.hr)

106 BTU/(ft2.hr)

10.00

4,993

3571 BTU/ft<sup>2</sup>

Av.Heat | Time (hrs)

884 BTU/(ft2.hr)

1314 BTU/(ft².hr)

BTU/(ft2.hr)

Thick. (in)

0.54

TIME (hours)

Product name

Cvcles/Year Lining area

Description

Proposed Lining

Ramp up HL @ 1650°F(B)

Ramp down HL @ 1650°F(F

Heat storage @ 2300°F(D)

1 FOAMFRAX GRADE I 2 IFB 2300F

Insulating Firebrick w/ Foamfrax Veneer

Product name

Soak HL @ 2300°F(D)

Fuel cost

Ramp up

Ramp down

xisting Lining Ramp up HL @ 1650°F(B)

Insulating Firebrick

Soak HL @ 2300°F(D)

Ramp down HL @ 1650°F(F)

Heat storage @ 2300°F(D)

# Foamfrax HD Applications

- Grade I, II, and III in a 12pcf-16pcf range
- Increased density from binder formulation and machine setting modifications
- Non-hydrated set, must be dried/fired



- Improved Installation times of kiln cars.
- Complex geometries can be molded.
- Use limit up to 2800° F.







## Foamfrax RG Applications

## <u>Advantages</u>

- Installation Rates of up to 900 Board Feet/Hr.
- Monolithic back-up material.
- Reduced material handling & cutting issues.
- Reduces Lining cross section
- 50% less dense and 3X more efficient than Light weight Castable.
- 1/6 the density and 10X more efficient than gunnite.







# **Case Study (RG Full Thickness)**

- Aluminum Re-heat oven
- 1000F Application

save energy, reduce pollution and Jimprove fire safety


- RG shot on 2 sides, arch and both doors
- Exterior insulation added to ducts
- Anchored using standard V anchors and steel wire mesh
- 4" FF RG replaced fiberwall construction
- Reheat times reduced from 4 hours to 2 hours
- After 6 months use, no issues.








- Operating temperature:1800°F
- Scope: 6" & 10" Foamfrax RG backup to gunnite.
- Anchoring System
  - > 304 SS studs with threaded ends for "V"
- Installation Date: February 2012
- Minimize cold face temp to minimize external insulation.







# Results











# Results

- Increased hopper volume due to decreased lining thickness.
- 18.4% of the Heat Loss of a traditional gunite system.
- Increased overall heat recovery of the system.
- Increase in installation rate.
- Minimal scrap (1%-3%) rebound loss.
- Reduced risk of reportable injury.







# FOGINGX MARKETS and APPLICATIONS





# **Target Markets**



#### Steel/Forge

- ➤ Roller Hearth Furnaces (Veneers, F.T., RG)
- **▶** Reheat Furnace Veneers
- **Ladle Stands**
- **➢ Over the Road Covers**
- **Coil Annealers**
- Continuous Annealing Line
- **▶** Batch Forge Furnaces
- ➤ Rotary Hearth Furnaces





# **Target Markets**

#### Ceramic

- **Low Mass Kiln Cars**
- > Tunnel Kiln Veneers
- **>** Sanitary Ware Refire Kiln
- **Periodic Kilns**

#### Aluminum


- > Furnace Doors
- Soaking Pit Veneers
- **▶** Back-Up Insulation







## **Target Markets**



#### Power

- > Steam Boiler Tubewall Exteriors
- > Co-Gen and Turbines
- **➢ Bio-Mass Steam Generation**
- **➤ Molten Salt Storage Tanks**
- Chemical Process Industry
  - **Ethylene Furnace Veneers**
  - > Ammonia Reformer Veneers
  - > RTO Full Thickness
  - > Heater Full Thickness





# **Target Applications**

- Veneer
  - **→** Fuel Savings
  - > Consumable Insulation
- Full Thickness
  - > Fast Turnaround
  - Special Applications/Geometries
- Back-Up
  - **➢ Behind Castable and Plastic**
  - **▶** Reduces Lining Thickness
  - Improves Insulation Properties







# Backup

- > Reduced lining cross section
- Reduced shell temperatures









# **Complex Geometries**

- > Improved rates
- Less manpower
- Safer installation












# **Quicker Rates**



Can a crew of 4 men cut and install 2" of backup board on this wall in 1 hour?

You can with Foamfrax!





# Veneer

- Dramatic fuel savings
- Cost effectiveness
- **Ease of installation**









# **Exterior Applications**

- **➢** Ground Flares
- **➤ Molten Salt Tanks**
- **Power Boilers**

save energy, reduce pollution and Jimprove fire safety





# Foanfrax University









# FOGINTIAX Questions?

Steener Cleaner Safety

specialty products that Safety
save energy, reduce pollution and improve fire safety



# Thank You For Considering Foamfrax & Foamfrax RG as a Heat Management Solution

